

receiving the clock signal a second input of a second flip-flop and at a second input of the first flip-flop;

12. The method for enabling a latch as recited in claim 11, wherein the step of transmitting the glitchless fractional clock pulse further comprises transmitting the glitchless fractional clock pulse from the output of the AND gate to the gate input of the latch.

of the first and second flip flops, a latch enable pulse is received on the first data input of the first flip flop, and a glitchless fractional clock pulse is generated on the output of the AND gate and transmitted to the storage enable input on the storage element.

16. An apparatus for storing data as recited in claim 13, wherein the glitchless fractional clock pulse generated at the logic output of the AND gate further comprises a glitchless fractional clock pulse having a width that is less than a width of a system clock pulse and positioned between a rising edge and a falling edge of the system clock pulse.

17. A network switch for switching data, said network switch comprising:
 at least one data port interface;
 at least one storage element in connection with the at least one data port interface and having a data input, a storage enable input, and a data output; and
 at least one logic circuit having an activating input, a clock input, and a logic output,

wherein the at least one logic circuit is configured to generate a glitchless fractional clock pulse on the logic output, said logic output being connected to the storage enable input of the storage element and operating to enable the at least one storage element to store data resident on the data input at an optimally stable time.

18. A network switch as recited in claim 17, wherein said network switch further comprises a communication channel in connection with the at least one data port interface for communicating data in the network switch.

19. A network switch as recited in claim 17, wherein said network switch further comprises a memory management unit for controlling the storage of data in the at least one storage unit.

20. An apparatus for storing data, said apparatus comprising:
 a storage means for storing data, said storage means having an input for receiving data to be stored, a storage enable input for enabling the storage means, and a data output; and

at least one pulse generating means for generating a glitchless fractional clock pulse, said pulse generating means having an activating input, a clock input,

21. An apparatus for storing data as recited in claim 20, wherein said storage means further comprises at least one latch.

a first flip flop having a first CLK input, a circuit enable input, and a first output;

an AND gate having a first input in connection with the first output of the first flip flop, a second inverted input in connection with the second output of the second flip flop, and an output,

wherein the glitchless fractional clock pulse is generated on the output of the AND gate upon receiving an enable pulse at the circuit enable input.